

# Cross Packaging Material Safety Data Sheet

## Cross Oil – Packaging Division

484 East 6<sup>th</sup> Street  
Smackover, AR USA  
71762

## Emergency:

870-881-8700, Ext. 1163

Information:

870-881-8700

Fax:

870-864-8656

Revision Date:

03/16/2011

### SECTION 1

### CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product:** Windshield Washer Solvent 0°F, Summer Formula  
**CAS Registry Number:** Not applicable for mixtures  
**Synonyms:** Windshield Washer Solution - Premixed, Windshield Washer Antifreeze and Summer Coolant, GlassGard Windshield Washer Solvent 0°F, Summer Formula, Xtreme Windshield Washer Solvent 0°F, Summer Formula  
**Item Number:** 568510  
**Generic/Chemical Name:** Alcohol solution/mixture.  
**Product Type:** Water Alcohol Solvent

### SECTION 2

### COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS #	%	ACGIH TWA	OSHA PEL	OSHA STEL	SKIN
Methanol	67-56-1	5 - 20	200 ppm	200 ppm	250 ppm	YES
Tetra-sodium EDTA	64-02-8	< 1	10 ppm	10 ppm	N D.	NO
Sodium Tetra-borate Penta-hydrate	1303-96-4	< 1	1 mg/m3	1 mg/m3	5 mg/m3	NO
Acid Blue 1 Mixture	129-17-9	< 1	N. D.	N. D.	N. D.	NO
Inert ingredients	Mixture	80 - 95	N. D.	N. D.	N. D.	NO

### SECTION 3

### HAZARDS IDENTIFICATION

**WARNING:** CONTAINS METHANOL  
CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.  
MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED.  
CANNOT BE MADE NONPOISONOUS

**Eye Contact:** Causes eye irritation and drying. Keep out of eyes.

**Skin Contact:** Avoid skin contact. Causes skin irritation. Harmful if absorbed through skin, causes damage to liver, kidney and nervous system.

**Inhalation:** Harmful if inhaled, causes damage to liver, kidney and nervous system. Causes nose and throat irritation.

**Ingestion:** May be fatal or cause blindness if swallowed. Cannot be made non-poisonous.

### SECTION 4

### FIRST AID MEASURES

**Eye Contact:** Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If irritation persists call a physician. If material is hot, treat for thermal burns and take victim to hospital immediately.

**Skin Contact:** Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs, seek medical attention. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately. Wash contaminated clothing before reuse.

WINDSHIELD WIPER FLUID 0F

Page 1 of 6

484 E. 6<sup>TH</sup> STREET • SMACKOVER, AR 71762 • PHONE 870-881-8700 • FAX 870-864-8656

## Cross Packaging Material Safety Data Sheet

<b>Inhalation:</b>	If inhaled remove to fresh air. If difficulty in breathing occurs, give oxygen, call a physician. Seek medical attention if irritation or discomfort persists.
<b>Ingestion:</b>	As little as 60 ml may cause blindness or fatality. Immediately give two glasses of water and induce vomiting. Call physician. Never give anything by mouth to an unconscious person.
<b>Note to physician:</b>	Provide standard methanol ingestion treatment. To prepare the antidote, make a solution using 100 ml of 100-proof ethyl alcohol (grain alcohol) in 2000 ml of water and give 1.5 ml per kg of body weight, or 100 ml for an average adult. Following this, at 2 hour intervals for 4 days, give the antidote (0.5 - 1.0 ml/kg of body weight) orally or intravenously to reduce the metabolism of the methanol and to allow time for its excretion. Blood ethanol levels should be maintained at 1.0 - 1.5 mg/ml.

### SECTION 5 FIRE FIGHTING MEASURES

<b>Flash Point:</b>	Min. 70°C (178°F) by Tag Closed Cup, ASTM D 56
<b>Upper Flammable Limit:</b>	Not determined
<b>Lower Flammable Limit:</b>	Not determined
<b>Extinguishing Media:</b>	Use dry chemical, alcohol foam, water spray, water fog or carbon dioxide if appropriate for the surrounding fire.
<b>Special Fire Fighting Procedures:</b>	Exercise caution when fighting any chemical fire. Evacuate affected area, stay upwind and avoid smoke and fumes. Use water spray to cool containers. If smoke and fumes cannot be avoided, a self-contained breathing apparatus and protective clothing are essential.
<b>Unusual Fire and Explosion Hazards:</b>	Flammable Liquid. Flame is invisible in daylight. Methanol-water mixtures will burn unless very dilute. Mixtures with 25% or more methanol are OSHA Class I flammable liquids. Follow appropriate National Fire Protection Association (NFPA) codes.
<b>By-products of Combustion:</b>	Thermal decomposition or combustion will produce carbon dioxide and water. Incomplete combustion may produce carbon monoxide
<b>Auto-ignition Temperature:</b>	Not determined
<b>Explosion Data:</b>	Not determined.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

<b>Spill Procedures (Land):</b>	Wearing appropriate personal protective equipment, contain spill, collect onto inert absorbent and place into suitable containers.
<b>Spill Procedures (Water):</b>	Completely water-soluble. Flush spill area with plenty of water. DO NOT flush to sewers. AQUATIC TOXICITY: 96 hour LC50 for fathead minnows is 28,100 mg/L.
<b>Waste Disposal Method:</b>	All disposals must comply with federal, state, and local regulations. CERCLA Reportable Quantity is 5000 pounds. The material, if spilled or discarded is a regulated RCRA hazardous waste number U154. May be disposed of by incineration, bio

### SECTION 7 HANDLING AND STORAGE

## Cross Packaging Material Safety Data Sheet

- Handling Procedures:** Keep away from heat, sparks or flame. Do not mix with strong oxidizers, chromic anhydride, lead perchlorate or perchloric acid. Avoid contact with eyes, skin and clothing. Avoid prolonged or repeated breathing of vapors. Use with adequate ventilation. Wash thoroughly after handling. Keep container tightly closed when not in use.
- Storage Procedures:** Keep away from heat, sparks or flame. Keep containers tightly closed. Do not store near strong oxidizers, chromic anhydride, lead perchlorate or perchloric acid. Store in adequately ventilated areas.
- Additional Information:** No additional information.

### SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

- Personal Protection:** Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.
- Respiratory Protection:** Good general ventilation should be provided to keep vapor concentrations below the exposure limits. When misting may occur in the work area, use a NIOSH approved respirator in accordance with respiratory requirements of OSHA 29 CFR 1910.134.
- Eye Protection:** Eye protection is always recommended. Use chemical splash goggles or face shield.
- Hand Protection:** Use of an apron or other protective clothing is recommended to avoid skin absorption. Launder soiled clothes.
- Other Protection:** Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials, which cannot be decontaminated.
- Local Control Measures:** Use adequate ventilation when working with material in an enclosed area. Use local exhaust ventilation where mist or spray may be generated. Eyewash stations and showers should be available in areas where this material is used and stored.
- Other:** This substance is a POISON. Consumption of food and drink must be prohibited in work areas where product is present. Always wash hands and face with soap and water before eating, drinking, or smoking.

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

- Vapor Pressure:** Negligible at STP (Standard Temperature and Pressure, 25°C at 1 ATM)
- Gravity by ASTM D 1298:**
- |                           |       |
|---------------------------|-------|
| API Gravity               | 10.5  |
| Specific Gravity @ 15.6°C | 0.996 |
| Density @ 15.6°C          | 8.30  |
- Solubility** Completely soluble in water, soluble in low molecular weight hydrocarbon solvents.
- Percent Volatile:** 15
- Vapor Density, Air = 1:** 1.1 at 25°C and 1 ATM (760 Torr)
- Evaporation Rate, n-Butyl Acetate = 1:** Greater than 1
- Odor:** Mild odor, irritates eyes

## Cross Packaging Material Safety Data Sheet

**Appearance:** Blue, translucent fluid  
**pH:** 7.8  
**Boiling Point:** 80°C (176°F)  
**Pour Point (°C):**  
by ASTM D 97 -18  
**Molecular Weight:** Not determined.

### SECTION 10 STABILITY AND REACTIVITY

**Stability:** Material is stable at room temperature and pressure.  
**Conditions To Avoid:** Do not store or mix with strong oxidizers, chromic anhydride, lead perchlorate or perchloric acid (reacts vigorously).  
**Incompatibility With Other Materials:** Avoid contact with acids and oxidizing materials.  
**Decomposition Products:** Thermal decomposition or combustion will produce carbon dioxide and water. Incomplete combustion will produce carbon monoxide.  
**Hazardous Polymerization:** Will not occur.

### SECTION 11 TOXICOLOGICAL INFORMATION

**Oral Toxicity:** Product oral LD50 (rat) = 9,150 mg per kg of body weight.  
**Dermal Toxicity:** Skin Absorption LD50 (rabbit) = 15,840 mg per kg of body weight.  
**Inhalation Toxicity:** Inhalation 1 hour LC50 (rat) = 145,000 parts per million.  
**Dermal Sensitization:** Prolonged or repeated contact may make skin more sensitive to other skin sensitizers. Based on data from similar materials.  
**Chronic Toxicity:** Methyl Alcohol is considered a chronic toxin.  
**Carcinogenicity:** No ingredients listed by IARC, NTP or OSHA.  
**Mutagenicity:** Not a mutagen..  
**Reproductive Toxicity:** Not determined.  
**Teratogenicity:** Not determined.  
**Other:** Not determined.

### SECTION 12 ECOLOGICAL INFORMATION

**Environmental Toxicity:** Aquatic Toxicity: The 96 hour LC50 for fathead minnows is 28,100 mg per Liter.  
**Environmental Fate:** No data available.

### SECTION 13 DISPOSAL CONSIDERATIONS

**Waste Disposal:** Discarded product as sold is a listed RCRA hazardous waste (U154). Waste management should be in full compliance with federal, state, and local laws.  
**Disposal Consideration:** Place used, spilled, contaminated, or excess material into disposable containers and dispose of with a licensed contractor in a manner consistent with local and state regulations.

### SECTION 14 TRANSPORT INFORMATION

#### U.S. DOT Information

WINDSHIELD WIPER FLUID 0F

Page 4 of 6

484 E. 6<sup>TH</sup> STREET • SMACKOVER, AR 71762 • PHONE 870-881-8700 • FAX 870-864-8656

## Cross Packaging Material Safety Data Sheet

**Bulk Shipping Description:** Methanol.

**Non-Bulk Shipping Description:** Methanol.

**Identification Number:** UN 1230.

**Hazard Classification:** Class 3 Flammable Liquid.

**Other:** See 49 CFR for additional requirements for descriptions, allowed modes of transport, and packaging. For more information concerning spills during transport, consult latest DOT Emergency Response Guidebook for Hazardous Materials Incidents, DOT P 5800.3.

### SECTION 15 REGULATORY INFORMATION

**Clean Water Act/Oil Pollution Act:** Not applicable.

**TSCA:** All components of this material are listed in the U.S. TSCA Inventory.

**Other TSCA:** Not applicable.

**SARA Title III:**

Section 302/304	Extremely Hazardous Substances:	None
Section 311/312	<u>Hazard Categorization:</u>	
	Acute (immediate health effects):	YES
	Chronic (delayed health effects):	YES
	Fire (hazard):	YES
	Reactivity (hazard):	No
	Pressure (sudden release hazard):	No
Section 313	Toxic Chemicals:	Methanol

**CERCLA:**

For stationary sources - reportable quantity:	5,000 pounds.
Due to:	Methanol.
For moving sources - reportable quantity:	5,000 pounds.
Due to:	Methanol.

Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.

**California Prop. 65:** Not applicable.

### SECTION 16 OTHER INFORMATION

	NFPA 704	NPCA-HMIS	KEY
<b>HEALTH:</b>	1	2	0 = Minimal
<b>FIRE:</b>	2	2	1 = Slight
<b>REACTIVITY:</b>	0	0	2 = Moderate
<b>SPECIFIC HAZARD:</b>	FLAMMABLE	N/A	3 = Serious
<b>PROTECTION INDEX:</b>	N/A	B	4 = Severe

**Precautionary Labels:** CONTAINS ETHANOL  
 CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.  
 MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED.  
 CANNOT BE MADE NONPOISONOUS.

This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Cross Packaging must rely upon information provided by the material manufacturers or distributors.

# Cross Packaging Material Safety Data Sheet

Prepared by: David Collins  
File: Windshield Fluid 0F

---

INFORMATION PROVIDED IN THIS MSDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF CROSS PACKAGING'S KNOWLEDGE; HOWEVER, CROSS PACKAGING MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF INFORMATION HEREIN PRESENTED. CROSS PACKAGING ASSUMES NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.