

Material Safety Data Sheet

Ebonite Series (Black Oils)



Page 1 of 6
Revised: 06/10/2010
MSDS #: Ebonite

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Ebonite Series
General Uses: Process oil, Chemical Carrier, Wetting Agent
Product Description: Black Liquid, Hydrocarbon Odor.

MANUFACTURER:

Cross Oil Refining & Marketing, Inc.
484 East Sixth Street
Smackover, Arkansas 71762
MSDS prepared by: Clark B. Smith

EMERGENCY TELEPHONE NUMBERS

(870) 881-8700, Ext.1163 [USA]

(870) 881-8700, Ext. 1128

2. COMPOSITION INFORMATION

CHEMICAL FAMILY: Petroleum Hydrocarbon	Common Name: Black Oil	<u>% Vol.</u>
HAZARDOUS INGREDIENTS: None Known	Exposure Limits (Oil Mist):	100%
C.A.S. #: Grades M-90, M-100, H-150	ACGIH, TLV (ppm),	TWA
64741-56-6	OSHA, PELS (ppm)	5
All Other Grades	NIOSH, TWA (ppm)	5
64742-52-5 / 64742-53-6		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Black liquid. Mild hydrocarbon odor. Can burn in a fire.

POTENTIAL HEALTH EFFECTS:

INHALATION: Will not produce vapors unless heated to temperatures of ~300 °F.

EYE CONTACT: Irritating, but will not permanently injure eye tissue.

SKIN CONTACT: Prolonged or repeated contact may cause skin irritation.

INGESTION: Small amounts (tablespoonful) swallowed are not likely to cause injury. Larger amounts may cause nausea and vomiting. Consult a physician promptly.

CHRONIC (CANCER) INFORMATION: According to IARC Monographs, neither severely hydrotreated lube oil nor bitumen has shown sufficient evidence to be considered carcinogenic. Ebonite products are composed of these two components. Thus, these oils are **Unlabeled** in accordance with 29 CFR 1910.1200.

4. FIRST AID MEASURES

EYE CONTACT: Flush eyes with plenty of water for several minutes. Get medical attention if eye irritation persists.

SKIN: Wash skin with plenty of soap and water for several minutes. Get medical attention if skin irritation develops or persists.

INGESTION: If more than several mouthfuls have been swallowed, give two glasses of water (16 Oz.). Get medical attention.

INHALATION: If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or symptoms persist.

Material Safety Data Sheet

Ebonite Series (Black Oils)



Page 2 of 6
Revised: 06/10/2010
MSDS #: Ebonite

5. FIRE FIGHTING MEASURES

Flash Point, °F (Method)	See Section 9 (COC)
Ignition Temp. °F	Not Determined
Flammability Limits (%)	Not Determined

RECOMMENDED FIRE EXTINGUISHING AGENTS AND SPECIAL PROCEDURES

According to NFPA Guide, use water spray, dry chemical, foam, or carbon dioxide. Water or foam may cause frothing. Use water to cool fire exposed containers. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for persons attempting to stop the leak.

UNUSUAL OR EXPLOSIVE HAZARDS: None

6. ACCIDENTAL RELEASE MEASURES

Notify the appropriate authorities immediately. Contain spill, if possible. Avoid breathing vapor. Use self contained breathing apparatus or supplied air for large spills or in confined areas. Wipe up or use suitable absorbent material and shovel into appropriate container for disposal. Prevent entry into sewers or waterways. Avoid contact with skin, eyes or clothing.

7. HANDLING AND STORAGE

PRECAUTIONS: Minimum feasible handling temperatures should be maintained. Periods of exposure to high temperature should be minimized. Water contamination should be avoided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION: Chemical-type goggles or face shield recommended to prevent eye exposure.

SKIN PROTECTION: Workers should wash exposed skin several times daily with soap and water. Soiled clothing should be laundered or dry cleaned at least weekly.

RESPIRATORY PROTECTION: Airborne concentrations should be kept to lowest levels. If vapor is generated, use respirator approved by OSHA or NIOSH as appropriate. Supplied air respiratory protection should be used for cleaning large spills or upon entry into tanks, vessels, or other confined spaces. See Exposure Limit below.

VENTILATION: Must be adequate to meet exposure limits below.

EXPOSURE LIMIT (TOTAL PRODUCT):

5 mg/m³ for mineral oil mist over an 8 hour daily exposure (ACGIH).

Material Safety Data Sheet

Ebonite Series (Black Oils)



Page 3 of 6
Revised: 06/10/2010
MSDS #: Ebonite

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Black liquid. Mineral odor.
% VOC: Essentially Zero
FREEZING POINT: Not applicable
VAPOR PRESSURE: Insignificant @ atmospheric pressure
pH: Not available
SOLUBILITY IN WATER: Insoluble
VAPOR DENSITY (Air=1): 1+

<u>GRADE</u>	<u>VISCOSITY, cSt @ 100 °C</u>	<u>FLASH, °C (COC)</u>	<u>SPECIFIC GRAVITY</u>	<u>BOILING POINT., °C</u>
M-90	18.01	216	.925	>316
M-100	19.60	232	.925	>316
H-150	32.0	260	.949	>316
H-150T	25.0	260	.947	>316
H-150R	25.0	220	.947	>316
H-180	38.8	260	.952	>316
M-180	39.8	210	.951	>316
H-200	43	266	.954	>316
M-220	46	210	.956	>316
M-250	50.78	210	.958	>316
MV-127	60	227	.963	>316
OGI-330	328.4	275	.983	>316
3150	2800 (60°C)	282	.981	>316
GO-325	66.7	227	.971	>316

10. STABILITY AND REACTIVITY

- This material reacts violently with strong oxidizers.
- Evolves toxic levels of carbon monoxide, carbon dioxide, irritating aldehydes and ketones when heated to combustion.
- Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

TOXOLOGICAL INFORMATION (ANIMAL TOXICITY DATA)

Not Available

Material Safety Data Sheet

Ebonite Series (Black Oils)



Page 4 of 6
Revised: 06/10/2010
MSDS #: Ebonite

12. ECOLOGICAL INFORMATION

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress in birds and mammals through ingestion.

This product is rapidly biodegradable. Biodegradation is possible with 100 to 120 days in aerobic environments at temperatures above 70F (21C).

A film or sheen will cause discoloration of the water surface or adjoining shoreline.

13. DISPOSAL CONSIDERATIONS

This product has been evaluated for RCRA characteristics and *does not* meet the criteria of a hazardous waste if discarded in its purchased form. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This product is subject in service to chemical alteration which may render the resulting material hazardous.

14. TRANSPORT INFORMATION

<u>PRODUCT</u>	<u>DOT CLASS</u>	<u>PLACARD NO.</u>	<u>PACKAGING</u>
Elevated Temperature Material Liquid	9	UN3257	PG III

15. REGULATORY INFORMATION

TSCA: All components of this material are listed in the U.S. TSCA Inventory.

OSHA: IARC Monographs state that when laboratory animals are exposed to severely hydrotreated oils, such as these product(s), there is **insufficient evidence** for cancer. Thus, these oils are **Unlabeled** in accordance with 29 CFR 1910.1200.

SARA TITLE III

Section 302/304 Extremely Hazardous Substance	None
Section 313 Toxic Chemicals	None

CERCLA

Material Safety Data Sheet

Ebonite Series (Black Oils)



Page 5 of 6
Revised: 06/10/2010
MSDS #: Ebonite

16. OTHER INFORMATION

Hazard Ratings Recommended for Containers

<u>NFPA</u>	<u>HMS</u>
Fire 1	Health 1
Health 1	Flammability 1
Reactivity 0	Reactivity 0
Specific Hazard none	Personal Protection Index B

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Cross Oil Refining & Marketing Company, Inc. The data on this sheet is related only to the specific material designated herein. Cross Oil Refining & Marketing Co., Inc. assumes no legal responsibility for use or reliance upon these data.

NA = Not Available Not App. = Not Applicable

17. PRODUCT LABEL

Product Trade Name: Ebonite Series

Date: 5/15/08

Tank Car Number: NA

Cross Truck Loading Manifest No: NA

WARNING

Avoid Prolonged Breathing of Mist or Spray: Average exposure to airborne mist for an 8 hour workday should not exceed 5.0 milligrams of mist per cubic meter of air.

Avoid Eye and Skin Contact: Wear oil-impervious protective clothing. If clothes become contaminated, change to clean clothing after thoroughly washing exposed skin with soap and warm water.

FIRST AID

Inhalation: If overcome by fumes, remove from exposure immediately and call a physician.

Skin: Wash with warm water and soap until the exposed area is clean.

Eyes: Flush with water for at least fifteen (15) minutes. See physician if symptoms persist.

Ingestion: Do not induce vomiting. Obtain medical assistance. Small amounts that accidentally enter through the mouth should be rinsed out until no taste of it remains.

FIRE CONTROL

Use water spray or fog, chemical foam, dry powder or carbon dioxide.

Material Safety Data Sheet

Ebonite Series (Black Oils)



Page 6 of 6
Revised: 06/10/2010
MSDS #: Ebonite

17. PRODUCT LABEL (Continued)

SPILL / LEAK

Add absorbent (sand, sawdust, etc.) to the spill area. Contain spill. Advise State Environmental Protection Agency, if required. Put recovered material in an appropriate container and dispose of according to federal, state, and local regulations. For guidance call Cross Oil Refining & Marketing Co. at (870) 881-8700, Ext. 1163

STORAGE

Store in original or equivalent container. Store at the lowest practical temperature. Keep container closed when not in use. Do not apply heat or flame to the container
