

## Product Information



### **AntiFreeze / Coolant Concentrate**

---

#### DESCRIPTION

**Gard® Antifreeze / Coolant** is a concentrated low silicate fluid for use in radiators of automotive, heavy duty, and industrial equipment. This unique product protects against surfaces including aluminum and rubber parts.

**Gard® Antifreeze / Coolant** is formulated with ethylene glycol base antifreeze to prevent freezing and overheating and containing corrosion inhibitors to protect against rust and corrosion.

---

#### APPLICATION

Automotive, heavy duty trucks, off road equipment and other applications such as stationary engines as a year round anitfreeze and summer coolant.

---

#### BENEFITS

- May be used in aluminum or cast iron engines
  - Helps stop rust and corrosion
  - Compatible with all conventional antifreeze – coolants
- 

#### PERFORMANCE LEVELS

GM 1899 (cast iron)  
GM 1825M (aluminum)  
ASTM D-4985, D-3306, D-4340  
SAE J1034, J1941  
OEM low silicate requirements

---

#### TYPICAL PROPERTIES

		<b>Antifreeze Coolant Concentrate</b>
Specific Gravity at 15.6°C	D-1122	1.10 -1.145
pH Concentrate	D-1287	11.0 Max
Reserve Alkalinity	D-1121	10 min
Freeze Point (50%)C (F)	D-1177	-37(-34) Max
Foaming Tendency	D-1881	50 mL/3 Sec Max
Ash, % Mass	D-1119	1.5
Color	Visual	flourescent green

---

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Material Safety Data Sheets available on request.

---



**CROSS PACKAGING DIVISION**

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656

---