

Product Information



Global CVT Fluid

- **Continuously Variable Transmission Fluid**

**Ultra-Premium, CVT ATF To Cover Multiple Applications
Use In Most Domestic Or Import CVT Transmissions**

DESCRIPTION

SynGard™ Global CVT Fluid is an ultra-premium, synthetic automatic transmission fluid designed to service most foreign and domestic vehicles CVT equipped vehicles sold in the United States. Eliminates the need to stock multiple, limited use OEM brands.

SynGard™ Global CVT Fluid is recommended for use in virtually all belt driven CVT transmissions. This product provides engineered anti-shudder performance for smooth transfer of power in highly sophisticated variable drive transmissions found in many newest cars and SUV's. **SynGard™ Global CVT Fluid** provides outstanding long term service by providing exceptional anti-oxidation and anti-wear protection.

SynGard™ Global CVT Fluid is recommended for use in most all chain and belt driven CVT transmissions manufactured by Nissan, Toyota, Honda/Acura, Mitsubishi, Chrysler, Saturn, Subaru and Mini Cooper. **SynGard™ Global CVT Fluid** is also recommended for certain transmissions manufactured by Mercedes, Toyota, Suzuki, Mazda, Hyundai, Kia and others.

When **SynGard™ Global CVT Fluid** IS STOCKED ALONG WITH **SynGard™ Global ATF Fluid**, the two fluids will service virtually every transmission used in North America in passenger cars, light trucks and SUV's.

APPLICATION

- Nissan ; all requiring Nissan CVY NS-2 Fluid
- Honda ; all requiring Honda Genuine CVT Fluid or Honda Multimatic Fluid
- Chrysler ; all requiring Mopar® CVT+4 (VTF)
- Subaru; all requiring Dexron® CVT (VTF)
- Saturn; all requiring Dexron® CVT (VTF)
- Mitsubishi; all requiring Dia Queen CVTF-J1 or SP-III fluid
- Mini Cooper; all requiring Esso CVT EZL 799
- Hyundai / Kia ; all requiring SP III Fluids
- Toyota/Mazda/Daihatsu; all requiring TC Fluid
- Suzuki; all requiring NS-2 / TC Fluid
- Ford; all requiring CVT 23 Fluids
- Mercedes; all requiring CVT 28 or 236.20 fluids

BENEFITS

- Eliminates numerous special CVT ATF's, services virtually all domestic and foreign vehicles sold in North America
- Synthetic components give outstanding oxidation resistance and extended service life
- Mixes safely with all OEM fluids
- Proper frictional control for special cvt transmission requirements
- Outstanding anti-wear and anti-oxidation life



CROSS PACKAGING DIVISION

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656

Product Information

**PERFORMANCE
LEVELS**

Ford Motor Company
Chrysler Mopar®
Honda
Nissan
Mini Cooper
Mitsubishi
General Motors Corporation

CVT 23
CVT+4

Dexron® CVT

**TYPICAL
PROPERTIES****METHOD****CVT Fluid**

Color	Visual	Red
Specific Gravity at 15.6°C	D1298	0.8524
Viscosity, cSt at 40°C	D445	35.64
Viscosity, cSt at 100°C	D445	7.12
Viscosity Index	D2270	167
Flash Point, °C	D92	232
Pour Point, °C	D97	-45
Brookfield Viscosity (-40°C), mPa·s	D2896	18516

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Material Safety Data Sheets available on request.

DEXRON® and MERCON® are registered trademarks of General Motors and Ford Motor Company, respectively.

**CROSS PACKAGING DIVISION**

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656