

Product Information



High Mileage Motor Oil

*Premium Automotive and Light Truck Engine Oil
Designed to Reduce Engine Oil Leakage
For Vehicles With Higher Mileage*

DESCRIPTION

Xtreme® High Mileage Oils is formulated from high quality base oils and high performance engine oil additives Pour depressants and a viscosity index (VI) improver are included to provide optimized viscosity and fluidity over a wide range of ambient temperatures. **Xtreme® High Mileage Oils** includes a seal swell conditioner to help prevent leaks in higher mileage vehicles.

Xtreme® High Mileage Oils protects against sludge and engine rust and corrosion under high and low-temperature operating conditions.

APPLICATION

- Recommended for high mileage gasoline fueled vehicles and light duty trucks
- Requirements fo API SM, SL or SJ product or API CF or CD.
- Meet or exceeds the requirements of ILSAC GF-4

Consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

BENEFITS

- Outstanding wear protection under a wide variety of operating conditions
- Contains a seal swell additive to prevent or control seal leaks
- Extra cleaning performance to help prevent the formation of sludge and harmful deposits

TYPICAL PROPERTIES	Method	5W-20	5W-30	10W-30
API Gravity	D 4052	31.8	31.8	31.4
Viscosity cSt @ 40°C	D 445	53.1	73.8	69.8
Viscosity cSt @ 100°C	D 445	9.1	12.1	11.3
Viscosity Index	D 2270	152	162	154
Cold Crank Simulation (cP)	D5293	5139 @ -30°C	6464 @ -30°C	4506 @ -25°C
NAOCK Volatility (%)	D 5800	14.0	14.6	12.7
Pour Point °C	D 97	-39	-39	-41
Flash Point, COC °C	D 92	212	216	228

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health and Safety Information See separate Material Safety Data Sheets available on request.



CROSS PACKAGING DIVISION

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656