

Product Information



High Performance Heavy Duty Mono-grade SM Engine Oils

*Premium Quality Gasoline Engine Oils
Meet or Exceed OEM Requirements, API Service SM*

DESCRIPTION

Xtreme® Mono-grade Engine Oils are exceptionally versatile premium quality straight grade crankcase oils for gasoline engines. Manufactured from selected premium, high viscosity index base stocks and formulated for outstanding performance in severe service and under varying operating conditions.

APPLICATION

Recommended for gasoline engines in automotive and industrial applications where straight grades oils are preferred, including cars, trucks, industrial engines, lawn and garden engines, pump engines and farm tractors.

BENEFITS

Xtreme® Engine Oils provide antiwear, rust and corrosion protection, resist oxidation, sludge and varnish deposits, protect against friction and wear, prevent foam, maintain low temperature fluidity while providing excellent high temperature lubrication with reduced volatility. Mono-grades stay in grade throughout their useful service life.

PERFORMANCE LEVELS

Certified to API Service Level SM,
SL, SJ, and SH

TYPICAL PROPERTIES

METHOD

		SAE 30	SAE 40
SAE Viscosity Grade	J300		
Viscosity , cSt @ 40C	D 445	89.2	159.8
Viscosity, cSt @100°C	D 445	10.5	15.6
Viscosity Index	D2270	102	99
Pour Point, °C.	D 97	-21	-10
Flash Point, °C	D 92	232	232
TBN (neutralization no.)	D 2896	7.0	7.0

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Material Safety Data Sheets available on request.



CROSS PACKAGING DIVISION

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656