

Product Information



Multi-Purpose EP2 Grease

Lithium-12 Hydroxy Stearate Base

Water Resistant and Excellent Rust Protection

DESCRIPTION

Gard® Multi-Purpose EP2 Grease is designed for a wide variety of automotive and industrial applications where a multi-purpose NLGI #2 Extreme Pressure grease is recommended. Gard® Multi-Purpose Grease is formulated with a premium Extreme Pressure, Anti-wear and Rust & Oxidation additive package in a Lithium Stearate mixed base thickener.

APPLICATION

Recommended for automotive, truck, and off-road equipment in ball joints, universal joints, king pins, bushings, roller bearings, chassis lubrication and fifth wheel lubricant, as well as industrial plain, friction, and roller bearings operating at normal temperatures and speeds, and service in contaminating environments. This grease will satisfy 80% of automotive and industrial applications.

BENEFITS

- Superior Extreme Pressure (EP) performance.
- Lithium/Calcium mixed base thickener compatible with most greases
- Water insoluble
- High Loading and Shock Loading capabilities

PERFORMANCE LEVELS

NLGI Rated LBGC for Automotive Chassis Usage

TYPICAL PROPERTIES

	METHOD	TYPICAL RESULTS
NLGI Consistency		2
Thickener		Lithium-12 Stearate
Texture		Smooth, Tacky
Color, Observed		Blue
Worked 60 Penetration	D-217	265-295
Dropping Point, °C. (°F)	D-2265	185 (365) Min.
Water Washout @ 100°F	D-1264	5.0
Timken OK Load, lb	D-2509	50
Four-Ball EP Weld Point, kgf	D-2596	300 (250 Min)
Approximate Temperature Range, °C, (°F)		-18 to 129 (0 to 265)

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Material Safety Data Sheets available on request.



CROSS PACKAGING DIVISION

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656