

Product Information



Special Blend 20W-50 Engine Oil

*Gasoline & Diesel Engine Oils For Heavy Duty Applications
Fleet Farm, Fleet, Off-Road All Purpose Oil
API CI-4, CF / SM Ratings*

DESCRIPTION

Xtreme® Special Blend 20W-50 Engine Oil is exceptionally versatile, premium quality, multi-grade crankcase lubricants giving outstanding performance in both diesel and gasoline engines in severe service and various operating conditions. Formulated Using state-of-the-art additives and Group II base oils to meet current API and OEM requirements for volatility and oxidation resistance.

Meets API level CI-4 requirements for improved oxidation stability, soot control, roller follower wear limits and reduced aeration. Meets OEM specifications where API CI-4 oils are recommended. OEM approved additive system offers maximum engine protection under widely varying operating conditions.

APPLICATION

- Over-the-road fleets, municipal service and school district bus fleets
- Automobiles, light and medium duty trucks with diesel or gasoline engines
- Stationary engines powering pumps, generators and drilling rigs
- Construction and farm equipment such as tractors, dozers, front end loaders, excavators
- Logging equipment such as skidders, feller bunchers , harvesters, loaders

BENEFITS

- Full film lubrication at operating temperatures
- Excellent low temperature flow properties for startup and cold weather use
- Outstanding soot control for new egr engines
- Exceptional engine cleanliness
- Outstanding anti-wear, oxidation control and friction control

PERFORMANCE LEVELS

API CI-4, CF /SM
Mack EO-N Premium Plus, EO-M Plus
Cummins CES 20078, 20076, 20071
Detroit Diesel Series 50, series 60
Volvo VDSs, VDS 2
Allison C-4



CROSS PACKAGING DIVISION

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656

Product Information

| TYPICAL PROPERTIES | METHOD | 20W-50 |
|----------------------------|--------|------------|
| API Rating | | CI-4 CF/SM |
| API Gravity | D 4052 | 28.2 |
| Specific Gravity at 15.6°C | D 1298 | 0.886 |
| Viscosity, cSt at 100°C | D 445 | 168.4 |
| Viscosity, cSt at 40°C | D 445 | 19.3 |
| Viscosity Index | D 2270 | 131 |
| Flash Point, °C | D 92 | 242 |
| Pour Point, °C | D 97 | -15 |
| Ash, % Sulphated | D 874 | 1.25 |
| TBN | D 2896 | 10.0 |

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Material Safety Data Sheets available on request.



CROSS PACKAGING DIVISION

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656