

Product Information



Full Synthetic 295 Heavy Duty Transmission Fluid

Heavy Duty, Transmission Fluid Using PAO Technology
Extended Oil Drain Intervals Pp to 50,000 Miles for Severe Service
Extended Oil Drain Intervals Up to 100,000 Miles for Regular Service
Meets Requirements Of Allison Transmission TES 295 Specification

DESCRIPTION

SynGard™ Full Synthetic 295 Heavy Duty Transmission Fluid is full PAO synthetic transmission fluid where Allison TES-295 specification or equivalent s required. The synthetic base oil provides high performance in the harshest of operating conditions. The high viscosity index and shear stability protects transmissions against thermal breakdown at high temperatures.

SynGard™ Full Synthetic 295 Heavy Duty Transmission Fluid is designed to meet the requirements of heavy duty automatic transmissions. It offers outstanding gear shifting and power transfer performance.

APPLICATION

- Heavy duty pickup trucks
- Commercial vehicles and trucks
- Emergency vehicles
- Off-road and on-road highway vehicles
- Municipal fleets, vans and school buses

BENEFITS

- High Viscosity Index
- Excellent shear stability, corrosion and foaming resistance
- Excellent low temperature properties
- Excellent thermal and oxidation stability

PERFORMANCE LEVELS

Allison Transmission	Allison TES 295 (AN - 051005)
Mercedes Benz	MB-Approval 236.91
Voith Transmission	Voith H55.6336.38
Voith ZF Driveline	ZF TE-ML 14B, 16L, 17C

TYPICAL PROPERTIES

	Method	FS 295 TF
Color	Visual	Red
Specific Gravity at 15.6°C	D1298	0.8388
Viscosity, cSt at 40°C	D445	34.30
Viscosity, cSt at 100°C	D445	7.36
Viscosity Index	D2270	188
Flash Point, °C	D92	220
Pour Point, °C	D97	-57
Brookfield Viscosity (-40°C), mPa·s	D2896	6069
Shear Stability	D6709	2.47



CROSS PACKAGING DIVISION

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656

Product Information

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Material Safety Data Sheets available on request.



CROSS PACKAGING DIVISION

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656