

## Product Information



# Pure-Flo Tractor Hydraulic and Transmission Fluid

*Universal Farm, Construction and Logging Lubricant  
For Transmission, Final Drive, Wet Clutch & Brake and Hydraulic*

---

### DESCRIPTION

**Xtreme® Pure Flo Tractor Hydraulic and Transmission Fluid** is a universal hydraulic and transmission fluid for farm tractors, construction equipment and logging equipment where a single fluid services the transmission, wet clutch, wet brake, power steering and final drives for two wheel and four wheel drive equipment.

**Xtreme® Pure Flo Tractor Hydraulic** is formulated using base oils specially selected for their resistance to oxidation, clarity and thermal stability. OEM approved drive-train additives are then added to enhance performance and provide extreme pressure (EP) protection for highly loaded gears and proper frictional characteristics needed for wet-clutches and brakes. Eliminates chatter common with many fluids. Separates water easily to prevent rust and corrosion inside gearboxes.

**Xtreme® Pure Flo Tractor Hydraulic** is a straight SAE 20 weight product and is designed for use in warmer climates, where low temperature operation is not an issue. Use Xtreme® Heavy-Duty Universal Tractor Hydraulic fluid for all-season or cold weather use.

---

### APPLICATION

- Farm tractors
- Construction equipment such as dozers, front end loaders, excavators
- Logging equipment such as skidders, feller bunchers , harvesters, loaders

---

### BENEFITS

- Protects gears with EP additives
- Inhibits rust, corrosion, and foaming and aids in water tolerance
- Mixes safely with all OEM fluids
- Proper frictional control for wet brakes and clutches
- OEM approved additive system

---

### PERFORMANCE LEVELS

John Deere	J20A, B (Hy-Gard), J14B (303 Fluid), J14C, J21A
Case/ IH	143, 145, MS-1204, MS-1205, MS 1206 - Hy-
Ford / New Holland	Tran, TCH
Massey Ferguson	ESN-M2C, 134B, C
Agco, White, Allis-Chalmers	PF821, M-1127, M-1129, Permatran, Q-1722
Caterpillar	TO-2



### CROSS PACKAGING DIVISION

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656

## Product Information

---

<b>TYPICAL PROPERTIES</b>	<b>METHOD</b>	<b>SAE 20</b>
Specific Gravity at 15.6°C	D 1298	0.926
Viscosity, cSt at 100°C	D 445	7.3
Viscosity Index	D 2270	52 Typ
Copper Strip Corrosion	D 130	1A
Foam, Sequence II	D 892	0 / 0
Flash Point, °C	D 92	191
Pour Point, °C	D 97	-32

---

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Material Safety Data Sheets available on request.



**CROSS PACKAGING DIVISION**

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ FAX 870 864-8656